

Casing Scrapers

Casing Scrapers

The Eaton CASING SCRAPER is ideal for removing cement, sheath, mud, scale, perforating burrs and other debris from the inside wall of the casing. The Eaton CASING SCRAPER can be run on drill pipe and can be used in a reciprocating manner or rotated. The CASING SCRAPER was engineered to eliminate all screws, bolts and blocks that might work loose in the hole and cause problems retrieving the scraper.

The Eaton CASING SCRAPER was designed with staggered blades giving a full 360 degrees of coverage. The blades are designed to be self-cleaning, while the angles prevent the blades from hanging up in casing collars.

The Eaton CASING SCRAPER assembly consists of five main parts; the main body, springs, blades and two sub ends. The spring mounted blades are located in the main body and are locked in place by the sub ends by means of 1/2" lips on each end that are fitted into machined recesses. The rotary-shouldered sub ends are then tightened to complete the assembly.

The Eaton CASING SCRAPER is available in the following sizes:

CASING SIZE	WEIGHT RANGE	CONNECTION
4 1/2" OD	9.50 thru 11.60	2 3/8" Reg Pin X Box
4 1/2" OD	11.60 thru 16.00	2 3/8" Reg Pin X Box
5" OD	13.00 thru 18.00	2 3/8" Reg Pin X Box
5 1/2" OD	14.00 thru 23.00	2 7/8" Reg Pin X Box
6 5/8" OD	17.00 thru 32.00	3 1/2" Reg Pin X Box
7" OD	19.00 thru 35.00	3 1/2" Reg Pin X Box
7" OD	38.00 thru 50.00	3 1/2" Reg Pin X Box
7 5/8" OD	26.00 thru 38.00	3 1/2" Reg Pin X Box
7 5/8" OD	39.00 thru 49.00	3 1/2" Reg Pin X Box
8 5/8" OD	24.00 thru 49.00	3 1/2" Reg Pin X Box
9 5/8" OD	29.00 thru 53.50	4 1/2" Reg Pin X Box
10 3/4" OD	32.75 thru 71.10	6 5/8" Reg Pin X Box
11 3/4" OD	38.00 thru 72.00	6 5/8" Reg Pin X Box
13 3/8" OD	54.50 thru 106.00	6 5/8" Reg Pin X Box
16" OD	55.00 thru 109.00	6 5/8" Reg Pin X Box
18" OD	78.00 thru 96.50	6 5/8" Reg Pin X Box
20" OD	94.00 thru 136.00	6 5/8" Reg Pin X Box
24" OD	100.00 thru 136.00	6 5/8" Reg Pin X Box



NO PROBLEMS



ONLY SOLUTIONS